




Integrated Device Technology, Inc.
2975 Stender Way, Santa Clara, CA - 95054

PRODUCT/PROCESS CHANGE NOTICE (PCN)

ATTACHMENT # 1 - PCN #: L0110-04

Moisture Sensitivity Label for level 3

	CAUTION This Bag Contains MOISTURE- SENSITIVE DEVICES	LEVEL 3 If Blank, see adjacent bar code label
<ol style="list-style-type: none">1. Calculated shelf life in sealed bag: 12 months at $< 40^{\circ}\text{C}$ and $< 90\%$ relative humidity (RH)2. Peak package body temperature: <input type="checkbox"/> 225°C <input type="checkbox"/> 240°C3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must<ol style="list-style-type: none">a) Mounted within 168 hours of factory conditions $\leq 30^{\circ}\text{C}/60\%$b) Stored at $\leq 10\%$ RH4. Devices require bake, before mounting, if:<ol style="list-style-type: none">a) Humidity Indicator Card is $>10\%$ when read at $23 \pm 5^{\circ}\text{C}$,b) 3a or 3b is not met.5. If baking is required, devices may be baked for 48 hours at $125 \pm 5^{\circ}\text{C}$		
<p>Note: If device containers cannot be subjected to high temperature or shorter bake times are desired, reference IPC/JEDEC J-STD-033 for bake procedure</p>		
Bag Seal Date : _____		
If Blank, see adjacent bar code label		
Note: Level and body temperature defined by IPC/JEDEC J-STD-020		